

## University of Groningen

### Advanced receivers for submillimeter and far infrared astronomy

Kooi, Jacob Willem

**IMPORTANT NOTE:** You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

*Document Version*

Publisher's PDF, also known as Version of record

*Publication date:*

2008

[Link to publication in University of Groningen/UMCG research database](#)

*Citation for published version (APA):*

Kooi, J. W. (2008). *Advanced receivers for submillimeter and far infrared astronomy*. [Thesis fully internal (DIV), University of Groningen]. [s.n.].

#### **Copyright**

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

#### **Take-down policy**

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

*Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.*

# **Advanced Receivers for Submillimeter and Far Infrared Astronomy**

## **Proefschrift**

ter verkrijging van het doctoraat in de  
Wiskunde en Natuurwetenschappen  
aan de Rijksuniversiteit Groningen  
op gezag van de  
Rector Magnificus, dr. F. Zwarts,  
in het openbaar te verdedigen op  
maandag 22 december 2008  
om 16:15 uur

door

**Jacob Willem Kooi**

geboren op 12 juli 1960  
te Geldrop

Promotores: Prof. dr. W. Wild  
Prof. dr. ir. T.M. Klapwijk

Beoordelingscommissie: Prof. dr. R. F. Peletier  
Prof. dr. M. W. M. de Graauw  
Prof. dr. V. Belitsky

ISBN 978-90-367-3653-4

*To my wife Helen*

*and my two sons*

*David and Andreas*



**Cover Front:** *Caltech Submillimeter Observatory on top of Mauna Kea, Hawaii. Photograph was taken by the author during full moon on October 12, 2006, at 3 o'clock in the morning. Exposure time was 61s, f/5.6, and ISO 200 sensitivity. Projected in the foreground is a high altitude balloon heading for the stratosphere to carry out atmospheric and astrophysical observations.*

– **Back:** *The Herschel space observatory pointed at star forming regions in M33 (the pinwheel galaxy) in the constellation Triangulum. The distance from our “own” galaxy, the Milky Way, to M33 is approximately 3 million lights years. To avoid attenuation from water in the Earth atmosphere, follow up astrophysical observations may eventually be carried out by aircraft such as Sofia, at low precipitable water vapor sites in Antarctica, the Atacama desert in Chile (not shown), Mauna Kea in Hawaii, and by future space missions.*

Copyright © 2008 by J. W. Kooi.

Printed by: PrintPartners Ipskamp B.V., Enschede, The Netherlands.

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Submillimeter and far-infrared astronomy . . . . .	1
1.1.1	Interstellar medium . . . . .	3
1.1.2	Star formation . . . . .	6
1.1.2.1	Molecular clouds . . . . .	6
1.1.2.2	Spectral line surveys . . . . .	8
1.1.3	Galaxies . . . . .	9
1.1.4	Solar system . . . . .	10
1.1.4.1	Planets . . . . .	10
1.1.4.2	Comets . . . . .	13
1.2	Coherent (heterodyne) detection . . . . .	14
1.2.1	Challenges . . . . .	14
1.2.2	Why high resolution spectroscopy . . . . .	16
1.3	Contribution to the field of far-infrared astronomical instrumentation	17
1.3.1	Thesis outline . . . . .	17
1.3.2	Impact on astronomy . . . . .	18
<b>2</b>	<b>Submillimeter detection and instrumental requirements</b>	<b>27</b>
2.1	Introduction/Overview . . . . .	27
2.2	Incoherent (direct) detection . . . . .	29
2.2.1	Bolometers . . . . .	30
2.2.2	TES . . . . .	32
2.2.3	Photon fluctuation noise . . . . .	32
2.2.4	Emissivity, optical efficiency, and sky noise . . . . .	33
2.2.5	Background limited detection . . . . .	34
2.2.5.1	Example 1: A 80 K space telescope . . . . .	34
2.2.5.2	Example 2: A 4 K (cooled) space telescope . . . . .	35
2.2.5.3	Example 3: A warm ground based telescope . . . . .	35
2.3	Coherent (heterodyne) detection . . . . .	35
2.3.1	Sensitivity of a heterodyne receiver . . . . .	38
2.3.2	Conversion of NEP to system noise temperature . . . . .	40
2.3.3	IF Bandwidth . . . . .	42
2.3.4	RF Bandwidth . . . . .	43
2.3.5	Instrument stability and baseline quality . . . . .	43

2.3.6	Calibration . . . . .	46
2.3.6.1	Two-load calibration . . . . .	46
2.3.6.2	One-load calibration . . . . .	48
2.4	Atmospheric transmission . . . . .	49
2.5	Summary . . . . .	52
<b>3</b>	<b>Heterodyne receiver concepts</b>	<b>57</b>
3.1	Mixing elements . . . . .	57
3.1.1	Schottky-diodes . . . . .	57
3.1.2	SIS tunnel junctions . . . . .	59
3.1.3	Hot electron bolometer mixers . . . . .	59
3.2	The single-ended Receiver . . . . .	59
3.3	The switched-load (Dicke) receiver . . . . .	61
3.4	The interferometer receiver . . . . .	62
3.5	The balanced receiver . . . . .	63
3.6	The correlation receiver . . . . .	63
3.7	The sideband separating receiver . . . . .	64
3.8	Summary . . . . .	65
<b>4</b>	<b>Fundamentals of SIS and HEB mixers</b>	<b>71</b>
4.1	SIS mixers: Introduction . . . . .	71
4.1.1	Photon-assisted quasiparticle tunneling . . . . .	72
4.1.2	The Josephson effect . . . . .	75
4.1.3	Network representation . . . . .	76
4.1.4	Current in an SIS junction . . . . .	77
4.1.5	Small-signal 3-port mixer model . . . . .	81
4.1.6	Noise properties . . . . .	83
4.1.7	SIS Mixer properties . . . . .	84
4.1.7.1	RF reflection coefficient . . . . .	84
4.1.7.2	IF output admittance and conversion gain . . . . .	85
4.1.7.3	Calculated receiver performance . . . . .	87
4.1.8	RF matching networks below the energy gap . . . . .	87
4.1.9	Sensitivity to operating temperature . . . . .	93
4.1.10	IF bandwidth . . . . .	96
4.1.11	SIS mixer stability as a function of magnetic field . . . . .	100
4.2	Electrodynamics and the non-local anomalous limit . . . . .	103
4.2.1	Transmission line model . . . . .	103
4.2.2	Plane waves in lossy dielectrics . . . . .	104
4.2.3	Plane waves in good conductors . . . . .	105
4.2.4	Surface impedance of normal metals . . . . .	106
4.2.5	Surface impedance of superconductors . . . . .	107
4.3	HEB mixers: Introduction . . . . .	110
4.3.1	Electro-thermal Feedback and IF Standing Waves . . . . .	115
4.3.2	Investigation of direct detection . . . . .	118
4.3.2.1	HIFI . . . . .	122
4.3.3	Effect on instrument calibration . . . . .	123

4.3.4	Parametric stability . . . . .	123
4.4	Summary . . . . .	125
<b>5</b>	<b>Quasi-optical mixers</b>	<b>137</b>
5.1	Introduction . . . . .	137
5.1.1	Waveguide Loss . . . . .	137
5.1.2	Absorption loss above the superconducting energy gap . . . . .	139
5.2	Physical implementation of a 850 GHz twin-slot mixer . . . . .	142
5.3	Optics . . . . .	143
5.4	Nb/AlN/NbTiN SIS junction with NbTiN wire layers . . . . .	144
5.5	Performance . . . . .	146
5.6	Astronomical observations . . . . .	147
5.7	Summary . . . . .	148
<b>6</b>	<b>IF impedance and mixer gain of NbN hot-electron bolometers</b>	<b>153</b>
6.1	Introduction . . . . .	154
6.2	Theory . . . . .	155
6.3	Experiment and calibration . . . . .	158
6.4	IF impedance . . . . .	160
6.5	Mixer conversion gain and the effect of electro-thermal feedback . . . . .	162
6.6	Increasing the IF bandwidth of hot electron bolometers . . . . .	165
6.7	Conclusion . . . . .	167
<b>7</b>	<b>A 275–425 GHz tunerless waveguide receiver based on AlN SIS technology</b>	<b>173</b>
7.1	Introduction . . . . .	174
7.2	Instrument design . . . . .	175
7.2.1	Broad bandwidth waveguide-to-microstrip Transition . . . . .	175
7.2.2	New set of SIS junctions . . . . .	177
7.2.3	Nb/AlN <sub>x</sub> -Al/Nb junction fabrication . . . . .	178
7.2.4	Multiple Andreev Reflection (MAR) . . . . .	180
7.2.5	Planar 4 – 8 GHz IF matching network, dc-break, bias Tee, and EMI filter . . . . .	181
7.2.6	4 – 8 GHz low noise cryogenic amplifier . . . . .	183
7.2.7	Cooled optics . . . . .	183
7.3	Receiver performance . . . . .	185
7.3.1	Fourier transform spectrometer measurements . . . . .	185
7.3.2	Heterodyne results and discussion . . . . .	185
7.3.3	IF response . . . . .	190
7.3.4	Stability . . . . .	191
7.3.5	Observations . . . . .	192
7.4	Conclusion . . . . .	194



<b>8</b>	<b>Advanced receiver implementations</b>	<b>201</b>
8.1	Introduction . . . . .	201
8.2	Balanced mixer theory . . . . .	202
8.2.1	The 180° balanced mixer . . . . .	204
8.2.2	Amplitude noise immunity of a 180° balanced mixer . . . . .	204
8.2.3	The 90° balanced mixer . . . . .	206
8.2.4	Amplitude noise immunity of a 90° balanced mixer . . . . .	207
8.3	Realization of 90° balanced-input receivers . . . . .	208
8.3.1	Improved quadrature-hybrid waveguide coupler . . . . .	209
8.3.2	Integrated IF and Wilkinson in-phase power combiner . . . . .	211
8.3.3	SIS Junctions with integrated IF matching . . . . .	214
8.3.4	Predicted performance . . . . .	214
8.4	The correlation receiver . . . . .	218
8.4.1	Introduction . . . . .	218
8.4.2	Theory . . . . .	218
8.4.2.1	Correlator back-end processor . . . . .	220
8.4.2.2	AOS back-end processor . . . . .	222
8.4.3	Observational analysis . . . . .	222
8.4.4	Physical implementation . . . . .	223
8.5	The sideband separating receiver . . . . .	224
8.5.1	Introduction . . . . .	224
8.5.2	Sideband separating mixer layout . . . . .	225
8.5.3	Theory . . . . .	226
8.5.4	SIS junction and waveguide transition simulations. . . . .	228
8.5.5	2SB computer simulations results . . . . .	230
8.5.6	Integrated planar IF . . . . .	231
8.5.7	Physical implementation . . . . .	232
8.5.8	Measurement results . . . . .	233
8.5.9	Atmospheric noise and the effect on 2SB and DSB receivers . . . . .	235
8.6	Summary . . . . .	237
<b>9</b>	<b>Towards integrated array receivers</b>	<b>245</b>
9.1	Introduction . . . . .	245
9.2	SIS mixer fabrication on 1 $\mu\text{m}$ thick $\text{Si}_3\text{N}_4$ membranes . . . . .	246
9.2.1	Device fabrication . . . . .	247
9.2.2	Measured performance . . . . .	248
9.3	HEB mixers on ultra-thin silicon substrates . . . . .	249
9.3.1	Introduction . . . . .	249
9.3.2	Silicon-On-Insulator (SOI) morphology . . . . .	251
9.3.3	SOI Processing . . . . .	253
9.3.4	“Symmetric” SOI-based waveguide transition . . . . .	253
9.3.5	“Asymmetric” SOI-based waveguide transition . . . . .	255
9.4	Large format arrays based on SOI technology . . . . .	257
9.4.1	Camera layout . . . . .	259
9.4.2	LO power distribution . . . . .	261
9.4.3	3 $\mu\text{m}$ thick silicon splitblock waveguide transition . . . . .	261

9.4.4	SIS junction design and predicted performance . . . . .	264
9.4.5	Tolerance to misalignment and fabrication . . . . .	267
9.4.6	Integrated IF . . . . .	268
9.4.7	Fourier transform spectrometer (FTS) measurements . . . . .	270
9.4.8	Heterodyne results . . . . .	272
9.5	Summary . . . . .	272
<b>10</b>	<b>Stability of heterodyne receivers at terahertz frequencies</b>	<b>279</b>
10.1	Introduction . . . . .	280
10.2	Stability of small volume HEB mixers . . . . .	282
10.2.1	Experimental setup . . . . .	282
10.2.2	Continuum stability . . . . .	284
10.2.3	Spectroscopic stability . . . . .	286
10.3	Atmospheric and mechanical receiver stability . . . . .	288
10.3.1	LO path length loss . . . . .	289
10.3.2	Standing waves in the LO – mixer path . . . . .	289
10.3.3	Estimate of allowed LO power fluctuations . . . . .	291
10.3.4	Sensitivity to atmospheric turbulence . . . . .	292
10.3.5	Sensitivity to mechanical fluctuations . . . . .	293
10.4	Experimental validation . . . . .	294
10.5	Conclusion . . . . .	295
<b>A</b>	<b>The Allan variance method</b>	<b>301</b>
A.1	Introduction . . . . .	301
A.2	Theoretical considerations . . . . .	302
A.3	Total Power Allan variance . . . . .	305
A.4	Spectroscopic Allan variance . . . . .	306
A.5	Improvement of spectroscopic over total power Allan variance . . . . .	307
<b>B</b>	<b>Transmission properties of Zitex</b>	<b>311</b>
B.1	Introduction . . . . .	311
B.2	Zitex G104, G106, G108, G110, G115, & A155 . . . . .	312
B.3	Multiple Layers . . . . .	313
B.4	Temperature Variation . . . . .	314
B.5	Refractive Index . . . . .	315
B.6	Thermal Conductivity . . . . .	315
<b>C</b>	<b>AR coated HDPE windows</b>	<b>319</b>
C.1	Introduction . . . . .	319
C.2	Antireflection coating . . . . .	321
C.3	Multi-layer antireflection coating . . . . .	321
	<b>Nederlandse Samenvatting</b>	<b>327</b>
	<b>Acknowledgements</b>	<b>333</b>

List of publications
----------------------

337
-----